REXOD

RXPO-C811





Technical Specifications

1. Printer Characteristics

- **Printer Method**
  Line thermal printing
- **Printer Speed**
  250mm/s (MAX)
- **Printer Resolution**
  203dpi
- **Effective printer width (TPH)**
  72mm (576dot)
- **TPH life**
  100km (Max)
- **Cutting method**
  Partial, Full
- **Feed method**
  Auto feeding
- **Printer Dimensions**
  195 x 145 x 143.3 (L x W x H)
- **Interface**
  USB+Bluetooth / USB+WIFI+Bluetooth
  USB+Ethernet / USB+RS232+Ethernet

2. Paper roll parameters

- **Paper roll type**
  Thermal receipt paper
- **Paper width**
  79.5± 0.5mm (MAX)
- **Paper roll diameters**
  80mm(MAX)
- **Paper thickness**
  0.06~0.08 ㎛

3. Detection function

- **TPH temper**
  Temperature sensor
- **Cover opening detection**
  Detect switch
- **Cutter home point detection**
  Reflective photoelectric sensor
- **Paper near end detection**
  Reflective photoelectric sensor
- **Black mark detection**
  Reflective photoelectric sensor
- **Paper output detection**
  Reflective photoelectric sensor

4. Power adaptor

- **Input**
  110-220V
- **Output**
  24V 1.7A DC±10%
- **Average current**
  1.7A (25% print ratio)
- **Peak current**
  8.5A (100% print ratio)

5. Reliabilty

- **Abrasion resistance**
  100km (MAX)
- **Pulse**
  100million
- **Cutter life**
  1,000,000 cuts

6. Character

- **Character requirements**
  ASCII 9X17, 12X24,
  GB18030 24X24
- **Size**
  ASCII 9X17, 12x24dots, 24x24dots
- **Print font**
  Font, highlight, invert, bold, height, width, underline
- **Barcorde type**
  UPC-A, UPC-E, JAN13(EAN13)
  JAN8(EAN8), CODABAR, ITF, CODE39
  CODE93, CODE128, QR CODE

7. Usage environment

- **Operating temperature**
  0℃~45℃
- **Using humidity**
  10~80%RH
- **Storage temperature**
  -10℃~60℃
- **Storage humidity**
  10-90%RH

8. Drivers & Commands

- **Drivers**
  Windows(WIN7,8,10,Vista,XP,2000)
  Ubuntu 12.04 32/64bit, MAC
- **Command**
  Compatible with POS/ESC command set

REXOD

Diameters

1. RXPO-C811

